NSN 5320-01-434-8679

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-434-8679 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.460 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.5817 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 1.018 inches and 1.109 inches Tip Diameter: 0.5500 inches Lubrication: Cetyl alcohol **Grip Length:** 1.875 inches **Thread Size:** 0.500 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-6-49 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-01-434-8679

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6-49 spec.