

View Online at <https://aerobasegroup.com/nsn/5320-01-435-2379>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

2.590 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.200 inches and 0.210 inches

**Width Between Flats:**

Between 0.2520 inches and 0.2555 inches

**Shank Diameter:**

Between 0.6074 inches and 0.6084 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.885 inches and 0.920 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

1.812 inches

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.562 inches

**Special Features:**

1/32 in oversize

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0