NSN 5320-01-435-3214

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-435-3214

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.708 inches

Head Style:

Err-090

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.6074 inches and 0.6084 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.885 inches and 0.920 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.9375 inches

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.562 inches

Special Features:

3/64 in oversize

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-435-3214

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

