

View Online at <https://aerobasegroup.com/nsn/5320-01-435-4191>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.645 inches

Head Style:

Err-090

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.5761 inches and 0.5771 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.842 inches and 0.877 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.875 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.562 inches

Special Features:

1/64 in oversize

Material:

Steel comp e4340 or steel comp 4130 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.