

View Online at <https://aerobasegroup.com/nsn/5320-01-435-6446>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.670 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.5454 inches and 0.5464 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.750 inches and 0.785 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.875 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Special Features:

3/64 in. Oversize

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.