# NSN 5320-01-435-9668

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.360 inches and 1.390 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

## Grip Length:

0.880 inches

# Thread Size:

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Surface Treatment:**

Anodize

#### Surface Treatment Specification:

Ti-shield iii, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-435-9668

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

