## NSN 5320-01-438-4486

Pin-rivet - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5320-01-436-4466
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.780 inches and 0.800 inches
Head Style:
Err-090
Head Height:
Between 0.045 inches and 0.055 inches
Width Between Flats:
Between 0.0781 inches and 0.0806 inches
Shank Diameter:
Between 0.2641 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.295 inches and 0.315 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
W/s: aircraft, osprey v-22a, air force; aircraft, intruder a-6e; aircraft, osprey v-22a, marine corps
Grip Length:
Between 0.495 inches and 0.505 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color code orange on thread end
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi hote 1, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

## NSN 5320-01-438-4486

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0