## NSN 5320-01-438-7136

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-438-7136 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.718 inches and 0.738 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0781 inches and 0.0806 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.423 inches and 0.443 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color code orange on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi hote 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5320-01-438-7136

Pin-rivet - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0