## NSN 5320-01-439-3770

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-439-3770



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.185 inches

### Head Style:

Flush countersunk

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

#### Grip Length:

0.750 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Color coded white

#### Material:

Titanium alloy uns r56400

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Hi-kote 1, specification 294, cagec 73197 mfr ref single treatment response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-439-3770

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

