## NSN 5320-01-439-5914

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-439-5914 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.123 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.435 inches and 0.460 inches **Grip Length:** 0.688 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color coded white on thread end Material: Titanium alloy uns r56400 **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Hi-kote 1, specification 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-439-5914

Pin-rivet - Page 2 of 2



Fiig:

A528u0