NSN 5320-01-444-6593

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-444-6593 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.360 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.375 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.000 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Grit blast on top of head; color coded white Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Ams4928 assn standard single treatment response or ams4967 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-444-6593

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0