NSN 5320-01-444-9225

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-444-9225 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 2.990 inches and 3.010 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol **Grip Length:** Between 2.495 inches and 2.505 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** Powder blast top of head, with color light blue on thread end. Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 76823-03a073 manufacturers standard Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-444-9225

Pin-rivet - Page 2 of 2



_						
ם ו	mil	11+2	riz	211	\sim	٦.
UC		IILa	114	аи	vi	и.

No

Fiig:

A528u0