# NSN 5320-01-445-0411

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-445-0411

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.985 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

## Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.2016 inches and 0.2026 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.375 inches

# Grip Length:

0.625 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.190 inches

## Shear Strength:

95000 single pounds per square inch

## **Special Features:**

Color coded white

## Material:

Titanium alloy

## **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

Hi-kote 1, specification 294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-445-0411

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

