# NSN 5320-01-445-4016

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-445-4016



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.223 inches and 1.263 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.061 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.398 inches and 0.413 inches

#### **End Application:**

F-16

### Grip Length:

Between 1.376 inches and 1.438 inches

#### Thready Qty Per Inch (tpi):

28

### Thread Size:

0.250 inches

#### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

#### Surface Treatment Specification:

Ams 2416 assn standard single treatment response

### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas4450 professional/industrial association standard

## Shelf Life:

N/a

# NSN 5320-01-445-4016

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

