## NSN 5320-01-446-7926

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-446-7926 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.997 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.435 inches and 0.460 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.562 inches Min. Tensile Strength (psi): 190000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color coded white Material: Titanium alloy uns r56400 **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, specification 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-446-7926

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0