NSN 5320-01-447-2564

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-447-2564 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 2.510 inches and 2.530 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.501 inches and 0.506 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.390 inches and 0.400 inches **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Hi-kote 1 hi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-447-2564

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0