

View Online at <https://aerobasegroup.com/nsn/5320-01-448-6200>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.315 inches and 1.335 inches

Head Style:

Flush countersunk

Hole Diameter:

Between 0.104 inches and 0.119 inches

Shoulder Diameter:

Between 0.1885 inches and 0.1895 inches

Shoulder Length:

1.2695 inches

Shank Diameter:

Between 0.181 inches and 0.184 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.258 inches and 0.305 inches

Hole Depth:

0.115 inches

Grip Length:

Between 0.995 inches and 1.005 inches

Thread Size:

0.190 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4130 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85, typ i mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.