

View Online at <https://aerobasegroup.com/nsn/5320-01-448-6200>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.315 inches and 1.335 inches

**Head Style:**

Flush countersunk

**Hole Diameter:**

Between 0.104 inches and 0.119 inches

**Shoulder Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shoulder Length:**

1.2695 inches

**Shank Diameter:**

Between 0.181 inches and 0.184 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.258 inches and 0.305 inches

**Hole Depth:**

0.115 inches

**Grip Length:**

Between 0.995 inches and 1.005 inches

**Thread Size:**

0.190 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 or steel comp 4130 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Bms10-85, typ i mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.