
NSN 5320-01-449-4431

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.015 inches and 1.025 inches

Head Style:

Flush countersunk

Hole Diameter:

Between 0.0947 inches and 0.0967 inches

Shoulder Diameter:

Between 0.2490 inches and 0.2495 inches

Shoulder Length:

Between 0.5611 inches and 0.5690 inches

Shank Diameter:

Between 0.2410 inches and 0.2440 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.358 inches and 0.365 inches

Hole Depth:

Between 0.130 inches and 0.150 inches

End Application:

F-15s

Grip Length:

Between 0.620 inches and 0.630 inches

Thread Size:

0.2500 inches

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-449-4431

Pin-rivet - Page 2 of 2

Fiig: A528u0

