## NSN 5320-01-449-5325

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Thread Direction:** 

Fastener Length:

Flush countersunk

Hole Diameter:

Between 0.883 inches and 0.893 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-449-5325

Between 0.0791 inches and 0.0806 inches
Shoulder Diameter:
Between 0.1890 inches and 0.1895 inches
Shoulder Length:
Between 0.5131 inches and 0.5210 inches
Shank Diameter:
Between 0.1810 inches and 0.1840 inches
Shank Style:
Err-090
Head Major Diameter:
Between 0.265 inches and 0.272 inches
Hole Depth:
Between 0.115 inches and 0.135 inches
End Application:
5-15s
Grip Length:
Between 0.558 inches and 0.568 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.1900 inches
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-449-5325

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0