NSN 5320-01-449-7785

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-449-7785

Thread	Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.800 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, eagle f-15; aircraft, galaxy c-5; aircraft, starlifter c-141

Grip Length:

1.4475 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.190 inches

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-449-7785

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

