

View Online at <https://aerobasegroup.com/nsn/5320-01-450-6586>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Brown

Fastener Length:

0.838 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.094 inches and 0.096 inches

Shank Diameter:

Between 0.217 inches and 0.218 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.322 inches and 0.330 inches

Lubrication:

Cetyl alcohol

End Application:

F/a-18 aircraft

Grip Length:

Between 0.433 inches and 0.443 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

(inavy) pin, rivet, fluted threads - shear, 100 degree c'sunk, hex point drive, 0.0312 oversize, cres (125 ksi fsu)

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0