## NSN 5320-01-450-6586

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-450-6586

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Brown
Fastener Length:
0.838 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.094 inches and 0.096 inches
Shank Diameter:
Between 0.217 inches and 0.218 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.322 inches and 0.330 inches
Lubrication:
Cetyl alcohol
End Application:
F/a-18 aircraft
Grip Length:
Between 0.433 inches and 0.443 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
(inavy) pin, rivet, fluted threads - shear, 100 degree c'sunk, hex point drive, 0.0312 oversize, cres (125 ksi fsu)
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

## NSN 5320-01-450-6586

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0