

View Online at <https://aerobasegroup.com/nsn/5320-01-450-6591>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.815 inches and 0.835 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.217 inches and 0.218 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.322 inches and 0.330 inches

Lubrication:

Cetyl alcohol

End Application:

F/a-18 aircraft

Grip Length:

Between 0.495 inches and 0.505 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Pin, riqet, fluted threads - shear, 100 degrees c'sunk, hex point drive, 0.0312 oversize, cres (125 ksi fsu)

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0