# NSN 5320-01-450-7306

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-450-7306

## Fastener Length:

Between 0.990 inches and 1.010 inches

## Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.093j inches and 0.096 inches

### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

0.1478 inches

### Head Minor Diameter:

0.086 mils and 0.096 centimeters

## **Countersink Height:**

0.021 inches

### End Application:

F-15s

## **Shear Strength:**

41000 single pounds per square inch

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

# Criticality Code Justification:

Agav

## Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy 7050

## **Material Specification:**

Qq-a-430 alloy 7050 federal specification single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification single treatment response

## **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-450-7306

Solid Rivet - Page 2 of 2

**Fiig:** A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

