NSN 5320-01-450-7306

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-450-7306

Fastener Length:
Between 0.990 inches and 1.010 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.093j inches and 0.096 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.1478 inches
Head Minor Diameter:
0.086 mils and 0.096 centimeters
Countersink Height:
0.021 inches
End Application:
F-15s
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Criticality Code Justification:
Agav
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 alloy 7050 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, cl 1 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5320-01-450-7306

Solid Rivet - Page 2 of 2



Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.