## NSN 5320-01-450-9581



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-450-9581 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.990 inches and 1.010 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.505 inches **Thread Size:** 0.312 inches **Special Features:** 6-32unjc-3b thread size along the longitudinal axis from the head end, 0.120 in. Slot lenght, 0.060 in. Slot width located on shank near head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-450-9581

Pin-rivet - Page 2 of 2



Fiig:

A528u0