

View Online at <https://aerobasegroup.com/nsn/5320-01-451-1041>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.627 inches and 0.647 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.217 inches and 0.218 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.322 inches and 0.330 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

F/a-18 aircraft

**Grip Length:**

0.312 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

(inavy) pin, rivet, fluted threads - shear, 100 degree c'sunk, hex point drive, 0.0312 oversize, cres (125 ksi fsu)

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0