

View Online at <https://aerobasegroup.com/nsn/5320-01-451-6832>

**Fastener Length:**

Between 0.552 inches and 0.572 inches

**Head Style:**

Undersized oval countersunk

**Head Height:**

Between 0.003 inches and 0.005 inches

**Shank Diameter:**

Between 0.124 inches and 0.127 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.1884 inches and 0.1957 inches

**Head Minor Diameter:**

0.134 mils and 0.144 centimeters

**Countersink Height:**

0.0286 inches

**End Application:**

F-15s

**Shear Strength:**

468 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Heat Treatment:**

T-73 solution heat treated

**Material:**

Aluminum alloy 7050

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.