## NSN 5320-01-451-6832

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-451-6832

Fastener Length:
Between 0.552 inches and 0.572 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.1884 inches and 0.1957 inches
Head Minor Diameter:
0.134 mils and 0.144 centimeters
Countersink Height:
0.0286 inches
End Application:
F-15s
Shear Strength:
468 single pounds per square inch
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Agav
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, cl 1 military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A040a0

## NSN 5320-01-451-6832

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.