NSN 5320-01-452-8910

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-452-8910

| Fastener Length: |
|--|
| 0.750 inches |
| Head Style: |
| Undersized oval countersunk |
| Head Height: |
| Between 0.003 inches and 0.005 inches |
| Shank Diameter: |
| Between 0.124 inches and 0.127 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| 0.1957 inches |
| Head Minor Diameter: |
| Between 0.134 inches and 0.144 inches |
| Countersink Height: |
| 0.0286 inches |
| End Application: |
| F-15s |
| Shear Strength: |
| 41000 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Criticality Code Justification: |
| Agav |
| Heat Treatment: |
| T-73 solution heat treated |
| Material: |
| Aluminum alloy 7050 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type ii, class i, clear military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |

NSN 5320-01-452-8910

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.