# NSN 5320-01-452-8910

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-452-8910

# Fastener Length:

0.750 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

0.1957 inches

## Head Minor Diameter:

Between 0.134 inches and 0.144 inches

#### **Countersink Height:**

0.0286 inches

## End Application:

F-15s

#### Shear Strength:

41000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

## Criticality Code Justification:

Agav

# Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy 7050

# Material Specification:

Qq-a-430 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type ii, class i, clear military specification single treatment response

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A040a0

# NSN 5320-01-452-8910

Solid Rivet - Page 2 of 2

# Mil-std (military Standard):

Mil-a-8625 spec.

