## NSN 5320-01-453-9101

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-453-9101



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.055 inches and 1.075 inches

## Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.435 inches and 0.460 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.620 inches and 0.630 inches

### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

5820 pounds per square inch

#### **Thread Size:**

0.250 inches

### Shear Strength:

9300 double pounds per square inch

#### **Special Features:**

Powder blast top of head

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-453-9101

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

