NSN 5320-01-453-9562

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-453-9562 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.473 inches and 2.498 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.5690 inches and 0.5695 inches **Head Major Diameter:** Between 1.008 inches and 1.097 inches **Expansion Device:** Threaded stem Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 1.745 inches and 1.755 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 27500 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 37300 double pounds per square inch **Countersink Angle:** Between 102.0 degrees and 103.0 degrees Material: Titanium alloy uns r56400 bolt **Material Specification:** II-t-8504 military specification 10th material response sleeve **Surface Treatment:** Passivate bolt **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response bolt **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-453-9562

Blind Rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A040a0

Mil-std (military Standard):

spec.