NSN 5320-01-454-0372



Solid Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-454-0372 Fastener Length: Between 0.115 inches and 0.135 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.155 inches and 0.158 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** Between 0.2396 inches and 0.2469 inches **Head Minor Diameter:** 0.185 mils and 0.195 centimeters

Countersink Height:
0.0372 inches

End Application:

F-15s

Shear Strength:

41000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Criticality Code Justification:

Agav

Special Features:

Color clear

Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy 7050

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

NSN 5320-01-454-0372

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.