## NSN 5320-01-454-0372



Solid Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-454-0372 Fastener Length: Between 0.115 inches and 0.135 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.155 inches and 0.158 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** Between 0.2396 inches and 0.2469 inches **Head Minor Diameter:** 0.185 mils and 0.195 centimeters

Countersink Height:
0.0372 inches

**End Application:** 

F-15s

**Shear Strength:** 

41000 single pounds per square inch

**Countersink Angle:** 

Between 99.5 degrees and 100.5 degrees

**Criticality Code Justification:** 

Agav

**Special Features:** 

Color clear

**Heat Treatment:** 

T-73 solution heat treated

Material:

Aluminum alloy 7050

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 2, cl 1 military specification single treatment response

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

## NSN 5320-01-454-0372

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.