## NSN 5320-01-454-2580

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-454-2580 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.562 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.306 inches and 0.313 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** F-15s **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded **Special Features:** Solid film lube Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-454-2580

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0