

NSN 5320-01-454-2581 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-454-2581 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.950 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.086 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.265 inches and 0.272 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** F-15s; w/s: aircraft, eagle f-15 **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** 

Pin-rivet, threaded

**Special Features:** 

Solid film lube

Material:

Steel comp xm-13

**Material Specification:** 

Ams 5629 assn standard single material response

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-454-2581

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0