

View Online at <https://aerobasegroup.com/nsn/5320-01-455-6470>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.198 inches and 1.218 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.4682 inches and 0.4732 inches

Head Minor Diameter:

Between 0.454 inches and 0.466 inches

Countersink Height:

Between 0.0918 inches and 0.0939 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.808 inches and 0.818 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0