## NSN 5320-01-456-0639

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-456-0639

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.742 inches

## Head Style:

Err-090

#### **Head Height:**

0.090 inches

#### Width Between Flats:

0.967 inches

#### Shank Diameter:

0.296 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.470 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

0.312 inches

### Min. Tensile Strength (psi):

5820 pounds per square inch

### Thread Size:

0.250 inches

### Shear Strength:

13100 double pounds per square inch

#### Material:

Steel

#### **Material Specification:**

Mil-s-5000 military specification single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5320-01-456-0639

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

