

View Online at <https://aerobasegroup.com/nsn/5320-01-456-8242>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.315 inches and 1.335 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2177 inches and 0.2182 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C17 aircraft

Grip Length:

Between 0.995 inches and 1.005 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

9500 double pounds per square inch

Product Name:

Pin-rivet threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-I-87132 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-87132 spec.