# NSN 5320-01-457-6900

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-457-6900



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.702 inches and 0.722 inches

# Head Style:

Flush countersunk

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

# Shank Diameter:

Between 0.2641 inches and 0.2651 inches

### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

# Grip Length:

Between 0.370 inches and 0.380 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

180000 pounds per square inch

#### Thread Size:

0.250 inches

#### Shear Strength:

1080000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Color yellow on thread end

#### Material:

Nickel alloy 718

#### Material Specification:

Ams 5662 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-457-6900

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

