

View Online at <https://aerobasegroup.com/nsn/5320-01-457-7661>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.313 inches and 2.333 inches

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.183 inches and 0.190 inches

Shank Diameter:

Between 0.437 inches and 0.439 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.582 inches and 0.676 inches

Grip Length:

Between 1.683 inches and 1.693 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.437 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Hi-kote 1 aluminum coating per hi-shear spec. 294, cetyl alcohol lube per hi-shear spec.305

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear spec. 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0