

View Online at <https://aerobasegroup.com/nsn/5320-01-457-7989>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.605 inches and 1.625 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0635 inches and 0.0645 inches

Shank Diameter:

Between 0.2172 inches and 0.2182 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.293 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.620 inches and 0.630 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.1640 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4340 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-s-5000 federal specification 3rd material response or mil-s-6049 federal standard 3rd material response or mil-s-5626 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.