# NSN 5320-01-458-0452

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-458-0452

## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 0.865 inches and 0.885 inches

## Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3115 inches and 0.3120 inches

## Shank Style:

## Head Major Diameter:

Between 0.472 inches and 0.505 inches

## Lubrication:

Cetyl alcohol

## End Application:

C-17

## Grip Length:

Between 0.370 inches and 0.380 inches

## Thready Qty Per Inch (tpi):

24

## **Thread Size:**

0.3125 inches

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

## Surface Treatment:

Aluminum

## Surface Treatment Specification:

Hi-kote 1, specification no. 294 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-458-0452

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

