## NSN 5320-01-458-0509

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-458-0509 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.490 inches and 1.510 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5569 inches and 0.5619 inches **Head Minor Diameter:** Between 0.542 inches and 0.555 inches **Countersink Height:** Between 0.1127 inches and 0.1198 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.3125 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response

**Surface Treatment:** 

Aluminum

## NSN 5320-01-458-0509

Pin-rivet - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Mil-I-87132 military specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-87132 spec.