NSN 5320-01-458-0636

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-458-0636 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.2025 inches and 1.2225 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.8075 inches and 0.8175 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 9300 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-458-0636

Pin-rivet - Page 2 of 2



Fiig:

A528u0