## NSN 5320-01-458-0795

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Right-hand** 

**Thread Direction:** 

Fastener Length:

3a

View Online at https://aerobasegroup.com/nsn/5320-01-458-0795



## Between 1.990 inches and 2.010 inches Head Style: Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Shank Diameter: Between 0.3115 inches and 0.3120 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **End Application:** C17 Grip Length: Between 1.495 inches and 1.505 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.313 inches **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response Surface Treatment: Aluminum **Surface Treatment Specification:** Per hi-shear spec. 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-458-0795

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

