

View Online at <https://aerobasegroup.com/nsn/5320-01-458-1075>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.035 inches and 2.055 inches

Head Style:

Err-090

Width Between Flats:

Between 0.197 inches and 0.217 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.6862 inches and 0.6912 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 1.495 inches and 1.505 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

I-shear spec. No.294 (hi-kote 1 only) mfr ref 6th treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0