

View Online at <https://aerobasegroup.com/nsn/5320-01-458-1099>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.063 inches and 1.083 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.1510 inches and 0.1540 inches

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.6041 inches and 0.7969 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.433 inches and 0.443 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

14450 pounds per square inch

**Thread Size:**

0.438 inches

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0